



CMM5 Cluster Management Module

The CMM5 is the latest generation of solutions for the distribution of TDD Synchronization signals and Power over Ethernet in the Cambium Networks portfolio. The CMM5 is a modular design with individual 4-port power injectors and an optional controller used for remote management.

Key capabilities include:

- Support for Gigabit Ethernet (1000BaseT)
- Modular and scalable from 4 ports to 32 ports
- Direct +/- 48VDC input (optional AC/DC power supplies are available from Cambium Networks)
- Uses Cambium Networks uGPS for synchronization source
- Dual resilient power inputs
- Rack-mountable
- Secure remote management when used with the optional CMM5 Controller Module
- Support for PMP 450m (cnMedusa™)
- Future support for integration into cnMaestro™ for cloud or NOC-based management



C000000L556A
CMM5 Power and Sync Injector, 56V



C000000L500A
CMM5 Controller

SYSTEM COMPATIBILITY

| PRODUCT | POWER | SYNC |
|----------------|-----------|---------|
| PMP / PTP 450i | Yes - 56V | Yes |
| PMP 450m | Yes - 56V | Yes |
| PTP 670 | Yes - 56V | Roadmap |
| PTP 700 | Yes - 56V | Roadmap |

SPECIFICATIONS

56V POWER AND SYNC INJECTOR

| | |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model Number | C000000L556A |
| Interfaces | Four RJ-45 Gigabit Powered output ports "To Radios" Four RJ-45 Gigabit Data input ports "To Switch Array" One GPS timing port (RJ-12) – connection to uGPS One CMM5 USB Serial port for local administration One RJ-12 Daisy Chain port "IN" One RJ-12 Daisy Chain port "OUT" Two power input ports +/- 48 VDC (power supplies sold separately or use existing DC power source if available) |
| Power | Input Voltage: + or - 48 VDC Input Power Consumption: up to 400 watts (85% efficiency); 10A Fuse Output Voltage: +55 VDC Output Current: 0 - 1.8 A per channel Output Power: 0 - 90 Watts per channel |
| Operating Temperature | -40° C to +55° C (-40° F to +131° F), 90% humidity, condensing |
| Dimensions | 8.85" W x 15.75" D x 2.25" H (225 mm x 400 mm x 57 mm) |
| Unit Weight | 6.6 lbs. (3 kg) |
| Power Supply Options | N000000L101A – CMM5 600W Power Supply N000000L054B – CMM5 240W Power Supply |

CONTROLLER

| | |
|----------------------|--------------------------------------------------------------------------------------------------------------|
| Model Number | C000000L500A |
| Data Interface | One RJ45 management port "Network" 4 each USB Ports "USB" – interface to Injector (only one port is used) |
| Power | Input Voltage: + or - 48 VDC Power Consumption: < 5 watts |
| Cabinet Temperature | -40° C to +55° C (-40° F to +131° F), 90% humidity, condensing |
| Management Interface | 10/100 BaseT RJ-45 http/https web-based management SNMPv2c/v3 |
| Dimensions | 8.75" W x 4.75" D x 1.70" H (222 mm x 122 mm x 42 mm) |
| Unit Weight | 1.0 lbs. (0.45 kg) |



N000000L101A
CMM5 600W Power Supply



C000000L054B
CMM5 240W Power Supply