

Point-to-Multipoint 54430 Access Point and Subscriber Module



The Motorola Wireless Broadband Point-to-Multipoint (PMP) 54430 Access Point and Subscriber Module is the ideal solution for developing, enhancing and extending advanced broadband networks with more than 45 Mbps of total aggregate throughput for data transfer, voice and video applications. The PMP 54430 Access Point and Subscriber Module provide wireless Line of Sight (LOS) and near Line of Sight (nLOS) broadband connectivity in the 5.4 GHz spectrum.

Motorola Wireless Broadband products combine field-proven toughness with exceptional performance, security, ease-of-use and cost effectiveness. PMP 54430 Series Access Point and Subscriber Modules are available with total throughputs greater than 40 Mbps for data, video and voice applications. PMP 54430 Subscriber Modules can be purchased with throughputs of 4, 10, 20 or 40 Mbps and throughput can be enhanced to existing modules via a fixed software license.

The PMP 54430 Access Point can be co-located on the same tower location with other Motorola PMP Access Point solutions. The user guide provides details on co-location planning and network design considerations.

FEATURE	INTEGRATED AP SPECIFICATION	SM SPECIFICATION
	CAP 54430	CSM 54430
MODEL NUMBER	5480AP, 5480APC	5490SM4, 5490SM10, 5490SM20, 5490SM40
PART NUMBER	5480CAA	5490AA, 5494AA
FREQUENCY RANGE	5470 - 5725 MHz	
CHANNEL WIDTH	5 MHz, 10 MHz or 20 MHz	
CHANNEL SPACING	Configurable on 2.5 MHz increments for 5 MHz Channel Configurable on 5 MHz increments for 10 and 20 MHz Channels	
ANTENNA GAIN	17 dBi (w/ included sector antenna)	10 dBi
TRANSMIT POWER (NOTE 1)	-30 to +21 dBm (to EIRP limit by region) (1dBm interval)	Auto transmit power control up to EIRP limit
MAX TRANSMIT POWER	21 dBm	19 dBm
EIRP	30 dBm FCC, ETSI (20MHz) 27 dBm FCC, ETSI (10MHz) 24 dBm FCC, ETSI (5MHz)	30 dBm FCC, ETSI (20MHz) 27 dBm FCC, ETSI (10MHz) 24 dBm FCC, ETSI (5MHz)
ANTENNA BEAM WIDTH	4 sector application (actual 3 dB antenna pattern: 60° horizontal 5° elevation; null fill)	55° horizontal 55° elevation 3 dB antenna pattern
ANTENNA CONNECTION	50 ohm N-type	N/A

**POINT-TO-MULTIPOINT 54430 ACCESS POINT
AND SUBSCRIBER MODULE**

FEATURE	INTEGRATED AP SPECIFICATION		SM SPECIFICATION
	CAP 54430		CSM 54430
MODULATION LEVELS (ADAPTIVE)	1X=QPSK, 2X=16QAM, 3X=64QAM		
FORWARD ERROR CORRECTION	¾ Reed-Solomon block coding		
PHYSICAL LAYER	OFDM 256FFT		
MAC (MEDIA ACCESS CONTROL) LAYER	Motorola Proprietary		
CYCLIC PREFIX	1/4, 1/8 or 1/16 fixed		
PPS	15,000		4,800
GPS SYNCHRONIZATION	Yes		
# OF SUBSCRIBERS PER SECTOR	Up to 200		N/A
ARQ	Yes		
QUALITY OF SERVICE	DiffServ QoS		
MAXIMUM DEPLOYMENT RANGE (W/ REFLECTOR DISH ON SM, LOS)	1X: 8 mi. (13 km), 2X: 6 mi. (10 km), 3X: 2.7 mi. (4 km)		
MAXIMUM AGGREGATE (UP+DOWN) THROUGHPUT PER SECTOR (@5 MHZ CHANNEL)	1X: 3.5 Mbps, 2X: 7 Mbps, 3X: 10.5 Mbps		
MAXIMUM AGGREGATE (UP+DOWN) THROUGHPUT PER SECTOR (@10MHZ CHANNEL)	1X: 8 Mbps, 2X: 16.5Mbps, 3X: 24.5Mbps		
MAXIMUM AGGREGATE (UP+DOWN) THROUGHPUT PER SECTOR (@20MHZ CHANNEL)	1X: 16.5 Mbps, 2X: 32 Mbps, 3X: >45 Mbps		
LATENCY	5-7 ms round trip		
ENCRYPTION	DES, FIPS 197 Certified AES Option		
NOMINAL RECEIVE SENSITIVITY (W/ FEC) @ 5 MHZ CHANNEL	1X: -93 dBm, 2X: -86 dBm, 3X: -79 dBm		
NOMINAL RECEIVE SENSITIVITY (W/ FEC) @ 10MHZ CHANNEL	1X: -90 dBm, 2X: -83 dBm, 3X: -76 dBm		
NOMINAL RECEIVE SENSITIVITY (W/ FEC) @ 20MHZ CHANNEL	1X: -87 dBm, 2X: -80 dBm, 3X: -73 dBm		
ETHERNET INTERFACE	10/100BaseT, half/full duplex, rate auto negotiated (802.3 compliant)		
PROTOCOLS USED	IPv4, UDP, TCP, IP, ICMP, Telnet, SNMP, HTTP, FTP		
NETWORK MANAGEMENT	HTTP, Telnet, FTP, SNMPv2c Prizm 3.3 and One Point Wireless Manager 2.2		
VLAN	802.1ad (DVLAN Q-in-Q), 802.1Q with 802.1p priority, dynamic port VID		
CE	EN 301 893 v1.5.1		
TEMPERATURE	-40°C to +55°C (-40°F to +131°F) 0% – 95% relative humidity, non-condensing		
WIND SURVIVAL	190 km/hour (118 mi/hour)		190 km/hour (118 mi/hour)
WIND LOADING	90 lbs.		45 lbs.
DIMENSIONS (H X W X D)	71 x 21 x 28 cm (28.75" x 8.25" x 11")		30 x 9 x 9 cm (11.75" x 3.4" x 3.4")
WEIGHT	6.1 kg (13.5 lbs.) (w/ antenna) 2.8 kg (6.1 lbs.) (w/o antenna)		0.45kg (1 lb.)
MAX POWER CONSUMPTION	19W		10W
INPUT VOLTAGE	24 to 59 V		24 to 30 V
COLLOCATION WITH PMP 52100	Yes		
COLLOCATION WITH PMP 54100	Yes, 10MHz guard band separation or 5MHz with 3 ft vertical required; synchronization required		
COLLOCATION WITH PMP 54400	Interoperable when using 10 MHz channel and ¼ cyclic prefix		
COLLOCATION WITH PMP 58100	Yes		



motorola.com/pmp

Printed in USA 5/10 MOTOROLA and the Stylized M Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. ©Motorola, Inc. 2010. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.