

XA4-240 Wi-Fi 5 Indoor Access Point

802.11ac Wave 2 High-Density Quad Radio AP with External Antennas

QUICK LOOK:

- **High-density design purpose-built for large venue deployments**
- **External antennas to support deployment-specific coverage requirements**
- **Software-defined radios support 4X the 5GHz capacity per AP**
- **EasyPass simplifies connectivity for Guest/BYOD/IoT**



The Xirrus XA4 High-Density Access Point (AP) with external antenna connectors is the highest capacity, plenum-rated Wi-Fi AP on the market and delivers massive scalability to meet the demands of today's mobile users. This indoor high-density AP features a powerful multi-core integrated controller, application-level intelligence, automated provisioning, and cloud or on-premises management.

The XA4-240 high-density AP provides the flexibility to connect various types of external antennas for unique coverages. This AP is ideal for providing robust wireless connectivity in locations such as convention centers, airports, train stations, bus stations, warehouses, and manufacturing facilities.

SOFTWARE-DEFINED FLEXIBILITY

Packed with performance, the XA4-240 quad radio AP supports software-defined radios (SDRs) to deliver up to 4 times the 5 GHz Wi-Fi capacity compared to competitive APs. Instantly boost performance with the click of a mouse to adapt to changing client devices and optimize the user experience.



EASY TO MANAGE

Combined with the Xirrus Management System (XMS), the XA4-240 series AP delivers complete visibility and control of the Wi-Fi network, including users, devices, applications, network traffic and the RF environment - all from a single console. Designed for simple deployment, zero-touch configuration gets your network up and running in just minutes.

XA4-240 High-Density External Antenna Access Point

Access Point Specifications

Radios 4 total: 3 - 5 GHz , 1 - 2.4 GHz / 5 GHz software programmable
4x4 11ac 3.47 Gbps
MU-MIMO: 16 streams

Wi-Fi 802.11 a/b/g/n/ac Wave 2

Channel Bonding Up to 160 MHz

Maximum Wi-Fi Bandwidth 13.88 Gbps

Wi-Fi Threat Sensor Yes

Antennas 16 RP-SMA female connectors

Maximum Associated Devices 960

Wired Uplinks -
SUPPORT FOUR MODES
802.3AD (AGGREGATE TRAFFIC), BROADCAST, LINK-BACKUP (FAILOVER), LOAD BALANCE
1 - 2.5 GbE, 1 - GbE

Maximum Power Consumption 46 W

Dimensions 33.02 cm (13 in)

Weight 2.49 kg (5.5 lbs)

Operating Temperature 0°C to 50°C (32°F to 122°F)
5-90% humidity, non-condensing

Storage Temperature -40°C to 70°C
(-40°F to 158°F)

* AP requires a future software release to support 160 MHz bonding

Network Specifications

RF Management

In-band spectrum analysis

Dynamic channel configuration

Dynamic cell size configuration

Monitor radio for threat assessment and mitigation wired and wireless packet captures (including all 802.11 headers)

Wired and wireless RMON / packet captures

Radio assurance for radio self-test and healing

RF monitor

2.4 & 5 GHz Honeypot control – Increase available

2.4 & 5 GHz wireless device density through management of spurious 2.4 & 5 GHz association traffic

Ultralow power mode – maximize wireless channel

Re-use and increase wireless device density through tight power controls

XA4-240 High-Density External Antenna Access Point

Network Specifications cont'd

High Availability

Supports hot standby mode for mission critical areas

In-service AOS software upgrade process increases network availability for 24x7 operations

Environmentally Friendly

Supports ability to turn off radios based on schedule

IPv6 Support (IN CLI ONLY)

IPv4 and IPv6 dual stack client support

IPv6-only network

Increase wireless device density through control of unnecessary IPv6 traffic over IPv4-only networks

IPv6 functions: IP addressing, DNS, filters, application control, syslog, SNMP management, SSH, Telnet, FTP, DHCP

RFC Support

RFC 768 UDP

RFC791IP

RFC 2460 IPV6 (Bridging only)

RFC 792 ICMP

RFC 793 TCP

RFC 826 ARP

RFC 1122 Requirements for Internet hosts – communication layers

RFC 1542 BOOTP

RFC 2131 DHCP

Security

WPA

IEEE 802.11i WPA2, RSN

RFC 1321 MD5 Message-digest algorithm

RFC 2246 TLS protocol version 1.0

RFC 3280 Internet X.509 PKI certificate and CRL profile

RFC 4347 Datagram transport layer security

RFC 4346 TLS protocol version 1.1

Encryption Types

Open, WEP, TKIP-MIC: RC4 40, 104 and 128 bits

Channel Support 2.4 GHz

(BASED UPON COUNTRY CODE SELECTIONS)

1,2,3,4,5,6,7,8,9,10,11,12,13,14

Channel Support 5 GHz

(BASED UPON COUNTRY CODE SELECTIONS)

U-NII-1 – Non-DFS channels 36 40 44 48

U-NII-2A DFS channels* 52 56 60 64

U-NII-2C DFS channels* 100 104 108 112 116 120 124 128 132 136 140 144

U-NII-3 Non-DFS channels 149 153 157 161 165

XA4-240 High-Density External Antenna Access Point

Management

Management	SNMP v1, v2c, v3	RFC 2819 Remote network monitoring management information base
	RFC 854 Telnet	RFC 2863 The Interface Group MIB
	RFC 1155 Management information for TCP/IP Based Internets	RFC 3164 BSD Syslog Protocol
	RFC 1156 MIB	RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)
	RFC 1157 SNMP	RFC 3416 Version 2 of the Protocol Operations for the Simple Network Management Protocol (SNMP)
	RFC 1212 Concise MIB definitions	RFC 3417 Transport mappings for the Simple Network Management Protocol (SNMP)
	RFC 1213 SNMP MIB II	RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)
	RFC 1215 A Convention for defining traps for use with the SNMP	RFC 3584 Coexistence between version 1, version 2, and version 3 of the Internet-standard network management framework
	RFC 1350 TFTP	RFC 3636 Definitions of managed objects for IEEE Xirrus Private MIBs
	RFC 1643 Ethernet MIB	Integration with Splunk for accurate search and analysis of intra-organizational IT events
	RFC 2030 Simple Network Time Protocol Sntp	Netflow Export v9 and IPFIX compatibility allows for IP traffic statistics collection
	RFC 2578 Structure of management information version 2 (SMIv2)	
	RFC 2579 Textual conventions for SMIv2	
	RFC 2616 HTTP 1.1	
	RFC 2665 Definitions of managed objects for the Ethernet-like interface types	
	RFC 2674 Definitions of managed objects for bridges with traffic classes, multicast filtering and virtual LAN extensions	

XA4-240 High-Density External Antenna Access Point

Receive Sensitivity¹

2.4 GHz	XA4-240
802.11b	
1 Mbps	-95
11 Mbps	-88
802.11g	
6 Mbps	-93
54 Mbps	-75
802.11n HT20	
MSC0	-91
MSC7	-72
802.11n HT40	
MSC0	-88
MSC7	-69

5 GHz	XA4-240
802.11a	
6 Mbps	89
54 Mbps	-74
802.11n HT20	
MSC0	-90
MSC7	-71
802.11n HT40	
MSC0	-87
MSC7	-68
802.11ac VHT20	
MSC0	-90
MSC9	-66
802.11ac VHT40	
MSC0	-87
MSC9	-61
802.11ac VHT80	
MSC0	-84
MSC9	-58
802.11ac VHT160	
MSC0	
MSC9	

¹Single radio chain

Standards

Wi-Fi Protocols	IEEE 802.11a, 802.11ac, 802.11b, 802.11d, 802.11e, 802.11g, 802.11h, 802.11i, 802.11j, 802.11k, 802.11n, 802.11u, 802.11w
Wired Protocols	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, 1000BASE-T, 802.3ab 1000BASE-T
	IEEE 802.1q – VLAN tagging
	IEEE 802.3ad – Link aggregation
	IEEE 802.1d – Spanning tree
	IEEE 802.1p – Layer 2 traffic prioritization
	IPv6 Control – Increase wireless device density through control of unnecessary IPv6 traffic on IPv4-only networks
	DHCP option 82

XA4-240 High-Density External Antenna Access Point

Ordering Information

Configured Models

XA4-240 Plenum-rated High-Density AP with external antenna connectors, consisting of four 3.47 Gbps capable 802.11ac (Wave 2) 4x4 MU-MIMO radios with integrated controller

Accessories

ANT-IN-DIRXX-4X4-RPSMA 30° and 60° 4x4 antenna for both 2.4 and 5 GHz frequency bands with RP-SMA connectors; Refer to External Antenna Guide for detailed specification

XP1-MSI-75 1 Port 75 W PoE injector for XA4-240. Requires order of appropriate XS-PWR-XX cord for the country where the AP will be deployed

Mounting Brackets Refer to Accessories Guide for options, part numbers and detailed information

Cambium XMS and Support

XMSC-SUB-2R-1 XMS-Cloud 1-year subscription: 2-radio AP with EasyPass Guest Self-Registration and Guest Ambassador modules and Cambium Care Advanced Support

XMSC-SUB-2R-3 XMS-Cloud 3-year subscription: 2-radio AP with EasyPass Guest Self-Registration and Guest Ambassador modules and Cambium Care Advanced Support

XMSC-SUB-2R-5 XMS-Cloud 5-year subscription: 2-radio AP with EasyPass Guest Self-Registration and Guest Ambassador modules and Cambium Care Advanced Support

EASY-SUB-2R-1 EasyPass 1-year subscription for a 2-radio AP operating with XMS-Cloud or XMS-Enterprise

EASY-SUB-2R-3 EasyPass 3-year subscription for a 2-radio AP operating with XMS-Cloud or XMS-Enterprise

EASY-SUB-2R-5 EasyPass 5-year subscription for a 2-radio AP operating with XMS-Cloud or XMS-Enterprise

CCADV-SUP-XA4-240-1 Cambium Care Advanced, 1-year support for one XA4-240 Wireless AP. 24x7 TAC support, SW updates, and NBD advance replacement for HW

CCADV-SUP-XA4-240-3 Cambium Care Advanced, 3-year support for one XA4-240 Wireless AP. 24x7 TAC support, SW updates, and NBD advance replacement for HW

CCADV-SUP-XA4-240-5 Cambium Care Advanced, 5-year support for one XA4-240 Wireless AP. 24x7 TAC support, SW updates, and NBD advance replacement for HW

CCPRO-SUP-XA4-240-1 Cambium Care Pro, 1-year support for one XA4-240 AP. 24x7 TAC support, SW updates

CCPRO-SUP-XA4-240-3 Cambium Care Pro, 3-year support for one XA4-240 AP. 24x7 TAC support, SW updates

CCPRO-SUP-XA4-240-5 Cambium Care Pro, 5-year support for one XA4-240 AP. 24x7 TAC support, SW updates

ABOUT CAMBIUM NETWORKS

Cambium Networks empowers millions of people with wireless connectivity worldwide. Its wireless portfolio is used by commercial and government network operators as well as broadband service providers to connect people, places and things. With a single network architecture spanning fixed wireless and Wi-Fi, Cambium Networks enables operators to achieve maximum performance with minimal spectrum. End-to-end cloud management transforms networks into dynamic environments that evolve to meet changing needs with minimal physical human intervention. Cambium Networks empowers a growing ecosystem of partners who design and deliver gigabit wireless solutions that just work.